



# T17 Specifications | Heavy-Duty High Performance Battery Rider Scrubber

## T17 洗地机规格 | 高性能驾驶式电瓶洗地机

### SCRUBBING SYSTEM

#### 洗地系统

Cleaning path   清洁宽度	40 in   1,015 mm
With scrubbing side brush   带洗地边刷	40 in   1,015 mm
With RH sweeping side brush (cyl scrub only)   带右侧扫地边刷 (仅适用于滚刷)	52 in   1,320 mm
With Dual sweeping side brush (cyl scrub only)   带双向扫地边刷 (仅适用于滚刷)	52 in   1,320 mm
Sweeping with Presweep   带预清扫刷	49.4 in   1,255 mm

#### Cylindrical main brushes

##### 主滚刷

Brush speed   刷头速度	500 rpm
Brush diameter (2)   刷头直径 (2)	9 in   230 mm
Brush down force (up to)   刷头向下压力 (最高达)	550 lb   250 kg
Brush motors-brushless (2)   无刷的刷头电机 (2)	1.5 hp   1.125 kW
Motor rating   电机等级	IP44
Debris hopper   碎屑垃圾箱容量	0.7 ft <sup>3</sup>   20 L

#### Disk main brushes

##### 主盘刷

Brush speed   刷头速度	315 rpm
Brush size diameter (2)   刷头尺寸直径 (2)	20 in   510 mm
Brush down force (up to)   刷头向下压力 (最高达)	550 lb   250 kg
Brush motor-brushless (2)   无刷的刷头压力 (2)	1.5 hp   1.125 kW
Motor rating   电机等级	IP44

#### Optional Presweep

##### 可选的预清扫功能

Debris capacity (overall)   碎屑容量(全部)	1.3 ft <sup>3</sup>   37 L
Filter bag capacity   过滤纸袋容量	1.0 ft <sup>3</sup>   28 L

#### Tanks

##### 容器

Solution tank   清水箱	75 gal   285 L
Recovery tank   污水箱	91.1 gal   346 L
Demisting chamber   除雾室	16.1 gal   61 L

Vacuum fan (Dual)   真空风扇 (两个)	2 x 0.8 hp   2 x 0.6 kW
-------------------------------	-------------------------

Speed   转速	14,500 rpm
Water lift   吸水高度	65 in   1,650 mm

### PROPELLING SYSTEM

#### 驱动系统

Propel speed forward (transport variable to)   向前驱动速度 (运输时可调至)	5.5 mph   9 km / h
Propel speed forward (scrubbing variable to)   向前驱动速度 (洗地时可调至)	4.0 mph   6.5 km / h
Propel speed reverse (variable to)   反向驱动速度 (可调至)	3 mph   5 km / h
Propel motor   驱动马达	3.0 hp   2.25 kW
Speed control   速度控制	Electronic – AC
Gradeability   爬坡能力	Base Unit   w/Ramp Kit 基本单位   w/Ramp Kit
Transport (empty for trailering)   运输 (空载时拖拽)	12 deg / 21%   12 deg / 21%
Transport at gross weight   以总重运输	7 deg / 12%   8.5 deg / 14.8%
Working (scrubbing)   工作时 (洗地)	5 deg / 8.7%   6 deg / 10.5%
Ground clearance (transport)   离地距离 (运输时)	2.5 in   64 mm
Tire front (1), non-marking   前轮胎 (1), 无标记	13.8 x 5.8 in   350 x 150 mm
Tires rear (2), non-marking   后轮胎 (2), 无标记	15 x 5 in   380 x 125 mm

### BATTERY SELECTIONS (est. continuous runtime: economy mode)

#### 电瓶的选择 (如. 持续正常运行时间: 经济模式)

#### Battery options

##### 电瓶池选项

Optional battery packages   可选电池组	(up to 3.5 hrs) 36V, 510 AH C/6 (up to 5.75 hrs) 36V, 750 AH C/6 (up to 7.5 hrs) 36V, 930 AH C/6
	(最长可工作 3.5 hrs) 36V, 510 AH C/6 (最长可工作 5.75 hrs) 36V, 750 AH C/6 (最长可工作 7.5 hrs) 36V, 930 AH C/6

#### Battery chargers available for all optional batteries

电瓶充电器可对所有的可选电瓶进行充电

**SOUND LEVEL****噪音水平**

Operator's ear:

操作人员耳朵听到的:

Disk: Mode #2*	65 dBA; Kpa 3 dBA
盘刷: 模式 #2*	65 dBA; Kpa 3 dBA
Cylindrical: Mode #2*	66 dBA; Kpa 3 dBA
滚刷: 模式 #2*	66 dBA; Kpa 3 dBA

Sound pressure level tested per IEC 60335-2-72

声压水平按照 IEC 60335-2-72 标准测试

\*Vacuum On, Squeegee Down, Brushes On, Brushes Up

真空开启, 吸水扒关闭, 刷头开启, 刷头向上

**MACHINE DIMENSIONS****机器尺寸**

Length Basic Machine	87.9 in   2,230 mm
机器基本长度	87.9 in   2,230 mm
Length with Pre-Sweep	113 in   2,870 mm
带预清扫刷的机器长度	113 in   2,870 mm
Width	
宽度	
Body	46 in   1,168 mm
机身	46 in   1,168 mm
Body (with Side Brush)	53 in   1,346 mm
机身 (带边刷)	53 in   1,346 mm
Rear squeegee (hard width)	49 in   1,245 mm
尾部吸水扒 (真实宽度)	49 in   1,245 mm
Height (top of Steering Wheel)	58.25 in   1,480 mm
高度 (方向盘的顶部)	58.25 in   1,480 mm
With overhead guard	82.5 in   2,096 mm
带机顶保护架	82.5 in   2,096 mm
Weight	
重量	
Empty (Base Unit)	1,925 lb   875 kg
空载 (基本单位)	1,925 lb   875 kg
With standard 510 AH batteries	3,365 lb   1,525 kg
配备标准的 510 AH 蓄电池	3,365 lb   1,525 kg
Gross Vehicle Weight (GVW)	5,940 lb   2,700 kg
机器毛重 (GVW)	5,940 lb   2,700 kg
Minimum aisle turn	93.25 in   2,370 mm
最小转弯直径	93.25 in   2,370 mm

**STANDARD FEATURES****标准功能**

1-Step™ One Button Scrub Operation	Onboard Diagnostics
1-Step™ 一键洗地操作	机载诊断系统
Touch-N-Go™ Wheel Mounted Module	Wheel Mounted Horn
Touch-N-Go™ 轮式安装的模块	轮式安装的边角

Recover Tank Full Indicator

污水箱水满指示灯

Solution Tank Empty Indicator

清水箱无水指示灯

Non Marking Drive Wheel

无标记的驱动轮

Yellow Maintenance Touch Points

黄色维护触点

Recovery Tank Debris Tray

污水箱碎屑托盘

In-Line Vacuum Fan Filter

内嵌的真空风扇过滤器

Swinging Rear Parabolic Squeegee

摆动式尾部抛物线型吸水扒

SmartRelease™ Breakaway Rear Squeegee

SmartRelease™ 分离式尾部吸水扒

Underwriters Laboratory (UL®) E Certified

获得 (UL®) E 类认证

**OPTIONAL EQUIPMENT****可选设备**

ec-H2O™ Solution System

采用电解活性水洗地技术的系统

Spray Hose (15 ft / 4.5 m) w/Retracting Reel

喷雾胶管 (15 ft / 4.5 m) w/可收回式盘轴

Vacuum Wand

真空吸嘴

Slide-Out Battery System

滑出式电瓶系统

Heavy-Duty Rear Squeegee Guard

高强度尾部吸水扒保护装置

Deluxe Seat w/Armrests &amp; Seatbelt

豪华座位、扶手和安全带

Headlights (LED)

车头灯 (LED)

High Traction Tire(s)

高牵引轮胎(s)

Fire Extinguisher

灭火器

Wheel Mounted Water Shut-Off

轮式安装水可以自动关闭

Full Wrap Steel Bumper

全环绕式钢制保险杠

Cushioned Stacked Corner Rollers (front)

堆叠式缓冲角落辊 (前端)

Manual Parking Brake

手动刹车制动器

Duramer™ Tanks &amp; Shrouds

Duramer™ 箱和护罩

Variable Flow Cuff Tank Drains

带流控口, 水箱排水可调

No-Tool Squeegee Change

更换吸水扒时无需使用工具

No-Tool Brush Change

更换刷头时无需使用工具

S.E. (Severe Environment) Switch

S.E. (苛刻环境) 开关

Solution Auto Fill System

溶液自动补充系统

Scrubbing Side Brush

洗地边刷

Sweep Side Brush (RH or Dual)

洗地边刷 (右侧或双向)

FOPS Certified Overhead Guard

获得 (FOPS) 认证的机顶保护架

Pre-sweep with Dry Dust Control

带有干尘控制功能的预清扫装置

Power Steering

电动驾驶

AV Backup Alarm (LED)

AV 倒车警报(LED)

Battery Watering System

电瓶注水系统

Underwriters Laboratory (UL®) Type ES Certified

获得 (UL®) ES 类认证

**WARRANTY****保修服务**

Please refer to your local Tennant representative for information.

如需了解更多详细信息, 请咨询当地坦能代表。

For a complete selection of genuine Tennant brushes and pads, please consult the T17 Parts and Consumables Reference Guide.

如需选择真正的坦能刷头和研磨垫, 请查阅 T17 洗地机零部件和耗材参考指南