

PRODUCT BULLETIN

High Alkaline Granular Degreaser

Heavy Duty Powder Degreaser



Tennant Company • 701 North Lilac Drive • Minneapolis, MN 55442
 800-553-8033 • www.tennantco.com
 © Tennant Company 03-02-2011

DESCRIPTION:

Tennant True High Alkaline Granular Degreaser is a low foaming high performance powder degreaser, specifically formulated for use in Tennant scrubbers.

USES:

- Heavy duty cleaning
- Can be used on both urethane or epoxy coated floors and uncoated floors
- Heavy manufacturing facilities
- Facilities with petroleum and grease

ADVANTAGES:

- Low foaming
- Designed specifically to be used with an automated scrubber and not damage critical parts of the machine.

STORAGE: Materials should be stored indoors between 65°F (18°C) and 90°F (32°C).

SHELF LIFE: 1 year from date of manufacture.

PACKAGING OPTIONS / PART NUMBERS:

22 pound carton (10 – 2.2 lb individual bags) / 9006782
 250 pound drum / 9006783

LIMITATIONS:

- Do not use on acrylic floor finish typically applied to VCT
- Do not use if soft metal filings are being picked up by scrubber

MATERIAL PROPERTIES (POWDER):

Property	Results
Color	White
Elemental Phosphate	None
Flash Point °F/C Seta Closed Cup	N / A
Foam	Low
Form	Powder
Freeze Point	N / A
Freeze/Thaw	Passes standard test of 3 freeze/thaw cycles
Odor	Soap
pH at 4 cups / 30 gal	12.3
pH at 4 cups / 15 gal	12.5
Solubility (Tap Water)	Soluble in water
Viscosity	Water thin
Wt. Per Gallon	17.53 lb/ gal.
Wetting Agents	Nonionic Surfactants

**DILUTION GUIDE FOR
TENNANT AUTOMATIC SCRUBBERS:**

LIGHT CLEANING:

Use 1 – 2.2lb bag or 4 cups per 30 gallons of warm water.

HEAVY CLEANING:

Use 1 – 2.2lb bag or 4 cups per 15 gallons of warm water.

Do not exceed 1 – 2.2 lb bag or 4 cups per 15 gallons of water dilution. If increased soil removal is needed explore additional brush / pad changes.

IMPORTANT: READ AND FOLLOW ALL PRECAUTIONS AND INSTRUCTIONS BEFORE PROCEEDING.



PLEASE SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR SAFETY INFORMATION AND PRECAUTIONS.

IMPORTANT: READ AND FOLLOW ALL PRECAUTIONS AND INSTRUCTIONS BEFORE PROCEEDING.

DIRECTIONS FOR USE

READ PRECAUTIONS ON LABEL BEFORE USING.

AUTOMATIC SCRUBBING

-  **Warning! Wear rubber or other impervious gloves and splash goggles when handling.**
-  **Warning! Follow appropriate floor safety procedures.**



Dilute the High Alkaline Granular Degreaser using the following dilution rates depending on the level of soilage. Pre-mix High Alkaline Granular Degreaser in a bucket with warm water and mix thoroughly.

Light Cleaning: Use 1 – 2.2 lb bag or 4 cups of High Alkaline Granular Degreaser per 30 gallons of warm water.

Heavy Cleaning: Use 1 – 2.2 lb bag or 4 cups of High Alkaline Granular Degreaser per 15 gallons of warm water.

Partially fill the solution tank with water. Pour the pre-mixed High Alkaline Granular Degreaser into the solution tank. Fill the solution tank with water until the level is just below the indicator level. Once the solution tank is filled with the appropriate dilution rate, scrub the floor according to the machine manual. After use, rinse solution tank and recovery tank to prevent soil build-up.

MANUAL SCRUBBING

-  **Warning! Wear rubber or other impervious gloves and splash goggles when handling.**
-  **Warning! Follow appropriate floor safety procedures.**

Dilute the High Alkaline Granular Degreaser using the following dilution rates depending on the level of soilage. Pre-mix High Alkaline Granular Degreaser in a bucket with warm water and mix thoroughly.

Light Cleaning: Use 1 – 2.2 lb bag or 4 cups of High Alkaline Granular Degreaser per 30 gallons of warm water.

Heavy Cleaning: Use 1 – 2.2 lb bag or 4 cups of High Alkaline Granular Degreaser per 15 gallons of warm water.

Apply the solution to the floor and scrub with a manual floor scrubber. Pick up solution with a mop or wet vacuum.

- * ***In federally inspected meat and poultry plants, always follow soilage pickup with a potable water rinse.***

PERSONAL PROTECTIVE EQUIPMENT

It is recommended that chemical splash goggles and impervious gloves (i.e. rubber) be worn when working with this material.

Improper use or dilution may cause increased health hazards, including eye and / or skin irritation and discomfort. May be harmful if swallowed. See Material Safety Data Sheet for additional information.

TECHNICAL SUPPORT / ORDERING

For any application questions or to reorder, please call Tennant Customer Service at 1-800-553-8033, or order online at www.tennantweblink.com.

DISPOSAL

Dispose in accordance with federal, state and local regulations. Please recycle the empty detergent container.

PLEASE SEE MATERIAL SAFETY DATA SHEET (MSDS) FOR SAFETY AND PRECAUTIONS.

USE PRODUCT AS DIRECTED.

KEEP OUT OF THE REACH OF CHILDREN.

WARRANTY

Tennant warrants this product to be free from defects of manufacture, improper formulations, and defective ingredients. Warranty covers replacement of material only.

THIS WARRANTY IS EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED, INCLUDING THE WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, AND OF ALL OTHER OBLIGATIONS AND LIABILITIES, INCLUDING LIABILITY FOR CONSEQUENTIAL DAMAGES OR CONTINGENT LIABILITIES ARISING OUT OF THE USE OF TENNANT MATERIALS.

No representative of Tennant has authority to give any other warranty or assume other liability. The presence of a Tennant employee during the application of material does not extend this warranty in any manner whatsoever.