



Safety Data Sheet

Part Number: 9017481, 9017483

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: ChemXP™-VE Crimson A

Chemical Family: Vinyl Ester Resin

Product Use: Coating material

Restrictions on Use: Use as directed by manufacturer

Manufacturer: Tennant Company
701 North Lilac Drive
P. O. Box 1452
Minneapolis, MN 55440-1452
Phone: 1-763-540-1200

24-Hour Emergency Phone Number: North America: 800-424-9300 (CHEMTREC)
International: 703-527-3887 (CHEMTREC) Collect Calls Accepted

2. HAZARD IDENTIFICATION

GHS Classifications

Health Hazards

Acute Toxicity, Inhalation, Category 4*
Skin Irritation, Category 2
Eye Irritation, Category 2A
Respiratory Sensitization, Category 1A
Skin Sensitization, Category 1A
Germ Cell Mutagenicity, Category 2
Carcinogenicity, Category 2
Reproductive Toxicity, Category 1B
Specific Target Organ Systemic Toxicity, Single Exposure, Category 3, Central Nervous System, Respiratory Tract [Inhalation, Ingestion, Skin contact]
Specific Target Organ Systemic Toxicity, Repeated Exposure, Category 1, Central Nervous System, Liver, Respiratory Tract [Inhalation, Ingestion, Skin contact]
Aspiration Hazard, Category 2

Physical Hazards

Flammable Liquid, Category 3

Environmental Hazards

Acute Aquatic Toxicity, Category 2

Safety Data Sheet

Part Number: **9017481, 9017483**

GHS-Labeling

Pictograms:



Signal Word: Danger!

Hazard Statements

H226: Flammable liquid and vapor
H305: May be harmful if swallowed and enters airways
H315: Causes skin irritation
H317: May cause an allergic skin reaction
H319: Causes serious eye irritation
H332: Harmful if inhaled
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335: May cause respiratory irritation
H336: May cause drowsiness or dizziness
H341: Suspected of causing genetic defects
H351: Suspected of causing cancer
H361: Suspected of damaging fertility or the unborn child
H372: Causes damage to organs through prolonged or repeated exposure
H401: Toxic to aquatic life

Precautionary Statements

Prevention:

P201: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. – No Smoking.
P233: Keep container tightly closed.
P235: Keep cool.
P240: Ground/bond container and receiving equipment.
P241: Use explosion-proof electrical/ventilating/lighting/equipment.
P242: Use only non-sparking tools.
P243: Take precautionary measures against static discharge.
P260: Do not breathe vapours.
P261: Avoid breathing vapours.
P264: Wash skin and exposed areas thoroughly after handling.
P270: Do not eat, drink or smoke when using this product.
P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.

Safety Data Sheet

Part Number: **9017481, 9017483**

P281: Use personal protective equipment as required.
 P285: In case of inadequate ventilation wear respiratory protection.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P302 + P352: IF ON SKIN: Wash with plenty of soap and water.
 P303 + P361 + P353: IF ON SKIN (hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 + P341: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308 + P313: IF exposed or concerned: Get medical advice/attention.
 P309 + P311: IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician.
 P314: Get medical advice/attention if you feel unwell.
 P321: Specific treatment found in supplemental First Aid section (Section 4) of this SDS.
 P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.
 P337 + P313: If eye irritation persists: Get medical advice/attention.
 P342 + P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
 P362: Take off contaminated clothing and wash before reuse.
 P363: Wash contaminated clothing before reuse.
 P370 + P378: In case of fire: Use dry chemicals, carbon dioxide, fog, alcohol foam or water spray for extinction.

Storage:

P403 + P233 + P235: Store in a well-ventilated place. Keep container tightly closed. Keep cool.
 P405: Store locked up

Disposal:

P501: Dispose of contents/container in accordance with local, regional, and federal regulations

* < 9% of this product consists of components of unknown acute inhalation toxicities

3. COMPOSITION/ INFORMATION ON INGREDIENTS

Chemical characterization

Vinyl Ester Resin

Component*	CAS #	% By Wt.
Styrene	100-42-5	35 – 50
Talc (Hydrous Magnesium Silicate)	14807-96-6	5 – 10
Naphtha, petroleum, light aromatic	64742-95-6	< 1
Dimethylaniline	121-69-7	< 1

Safety Data Sheet

Part Number: 9017481, 9017483

*The above listed components are OSHA hazardous materials which contribute to this products' GHS Hazard Categorization as prescribed in OSHA's Hazard Communication 29 CFR 1910.1200.

4. FIRST AID MEASURES

Inhalation

Symptoms & Effects: Stomach or intestinal irritation, nausea, headache, vomiting, diarrhea, irritation of the nose and airways, central nervous system depression, dizziness, drowsiness, weakness, fatigue, unconsciousness, lack of coordination, confusion

Measures: Immediately move outdoors or to fresh air. If breathing is difficult administer oxygen. Seek immediate medical attention and keep individual warm and quiet.

Skin Contact

Symptoms & Effects: Skin irritation, redness, burning sensation, drying, cracking, other skin damage

Measures: Immediately remove contaminated clothing. Flush exposed area with large amounts of water. Seek immediate medical attention. Wash contaminated clothing before reuse.

Eye Contact

Symptoms & Effects: Eye irritation, stinging sensation, tearing, redness, swelling of the eyes

Measures: Remove contact lenses and immediately flush eyes gently with plenty of water for at least 15 minutes. Rinse beneath eyelids by holding eyelids open with clean fingers while washing. Seek immediate medical attention.

Ingestion

Symptoms & Effects: Stomach or intestinal irritation, nausea, vomiting, diarrhea, metallic taste in the mouth and throat, irritation of the throat, central nervous system depression, dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness, lack of coordination, & confusion. Swallowing large amounts may cause for material to enter the lungs during swallowing or vomiting, leading to lung inflammation and other lung damages.

Measures: Seek immediate medical attention. If individual is drowsy or unconscious, have the individual lie down on their left side with their head down. Do not give individual anything by mouth. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. Do not leave individual unattended.

5. FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Dry chemical, Carbon dioxide, Water spray, Alcohol-resistant foam

Unsuitable Extinguishing Media: Water may be ineffective unless used under favorable conditions.

Hazardous Combustion Products: Phenols, Hydrocarbons, Carbon monoxide, Carbon dioxide

Safety Data Sheet

Part Number: **9017481, 9017483**

Protective Equipment for Fire-Fighters: Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

Precautions for Fire-Fighters: Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by any ignition source near the material. Never use a welding or cutting torch on or near the drum, even if empty, because product can ignite explosively. Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire-fighters. If performed under minimal risk, use water spray to cool fire-exposed containers and materials until fire is out. Avoid spreading burning material with water used for cooling purposes. Polymerization will take place under fire conditions. If polymerization occurs in a closed container, there is a possibility it will rupture violently.

6. ACCIDENTAL RELEASE MEASURES

Protective Equipment: Recommended to wear chemical splash goggles & resistant gloves, such as polyvinyl alcohol-based gloves, and discard of gloves that show tears, pinholes, or signs of wear. Wear proper garments to prevent skin exposure, such as long-sleeves and pants.

Personal Precautions: Persons not wearing proper PPE should be excluded from the area of contamination until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources and pay attention to the spreading of gases, especially at ground level.

Environmental Precautions: Do not allow discharge into drains, surface waters, or sanitary sewer system. Prevent spreading over a wide area by containment or oil barriers. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Methods & Materials for Clean-Up: Contained spilled material with inert, non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth, vermiculite). Transfer to a suitable container for disposal according to proper federal, state, and local regulations.

7. HANDLING AND STORAGE

Handling: Containers of this material may be hazardous when emptied since emptied containers retain product residues (vapor, liquid, or solid). Keep away from heat and ignition sources. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in the National Fire Protection Association (NFPA) document 77.

Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature or pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

Safety Data Sheet

Part Number: **9017481, 9017483**

Storage: Store in a cool, dry, ventilated area, away from heat and ignition sources as well as from incompatible materials (see below). Keep container tightly closed. Keep away from food, drink, and animal foodstuffs.

Incompatible Materials: Acids, Aluminum, Aluminum Chloride, Bases, Copper, Copper alloys, Halogens, Iron chloride, Metal salts, Strong oxidizing agents, Peroxides

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

Exposure Limits :

Exposure limits have not been established for this product.

Styrene	CAS # 100-42-5	
OSHA	Permissible exposure limit (PEL)	100 ppm
ACGIH	Time weighted average (TWA)	20 ppm
NIOSH	Recommended exposure limit (REL)	50 ppm (215 mg/m ³)

Talc (Hydrous Magnesium Silicate)	CAS # 14807-96-6	
OSHA	Permissible Exposure Limit (PEL)	20 mppcf
ACGIH	Time weighted average (TWA)	2 mg/m ³
NIOSH	Recommended Exposure Limit (REL)	2 mg/m ³

Dimethylaniline	CAS # 121-69-7	
OSHA	Permissible exposure limit (PEL)	5 ppm (25 mg/m ³)
ACGIH	Time weighted average (TWA)	5 ppm (25 mg/m ³)
NIOSH	Recommended exposure limit (REL)	5 ppm (25 mg/m ³)

Engineering Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposures below permissible exposure limits. OSHA has formally endorsed a styrene industry proposal for a voluntary 50 ppm workplace limit on styrene. Members of the Styrene Information and Research Council (SIRC), Composites Institute (CI), Composite Fabricators Association (CFA), International Cast Polymers Association (ICPA) and National Marine Manufacturers Association (NMMA) have agreed to use either engineering controls, work practices or respiratory protection to achieve this voluntary limit for styrene.

Occupational Exposure Controls: Ensure adequate ventilation, especially in confined areas. Consider all potential hazards of this material, applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting PPE. Ensure that eyewash stations and safety showers are proximal to the work location. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Safety Data Sheet

Part Number: **9017481, 9017483**

Protective and Hygiene measures: Do not inhale vapors. Wash hands before breaks and immediately after handling product. When using, do not eat, drink, or smoke. In case of clothes contamination, remove and wash contaminated clothing before re-use.

Eye Protection: Recommended to wear tight fitting, chemical splash goggles when there is potential for the exposure of the eyes to the liquid, vapor or mist. Have a suitable eye wash station or bottle nearby in case of splashing into the eyes.

Hand Protection: Recommended to wear resistant gloves, such as polyvinyl alcohol-based gloves and discard of gloves that show tears, pinholes, or signs of wear.

Skin Protection: Recommended to wear impervious clothing such as a full rubber suit and long-sleeved clothing, pants and proper foot covering in order to prevent direct skin contact with the product. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Red Liquid

Odor: Pungent

Odor Threshold: No data available

pH: No data available

Melting/Freezing point: No data available

Boiling point/range: > 284°F (> 140°C)

Flash point (Tag closed cup): 95°F (35°C)

Evaporation rate: No data available

Flammability: Lower Limit: 1.1% (V) **Upper Limit:** No data available

Vapor pressure: No data available

Relative vapor density: > 1 (Air = 1)

Density: 1.13 g/cm³ (9.4 lb/gal) @ 68°F (20°C)

Solubility in water: Insoluble

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available

Ignition temperature: No data available

Decomposition temperature: No data available

Viscosity (dynamic): No data available

Safety Data Sheet

Part Number: 9017481, 9017483

10. STABILITY AND REACTIVITY

Reactivity: No decomposition if stored and applied as directed.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Avoid exposure to excessive heat, peroxides and polymerization catalysts. Product will not undergo hazardous polymerization.

Conditions to Avoid: Heat, Flames, Sparks, Exposure to sunlight, Exposure to air

Incompatible Materials: Acids, Aluminum, Aluminum Chloride, Bases, Copper, Copper alloys, Halogens, Iron chloride, Metal salts, Strong oxidizing agents, Peroxides, UV light

Hazardous decomposition products: Phenols, Hydrocarbons, Carbon monoxide, Carbon dioxide

11. TOXICOLOGICAL INFORMATION

Primary Routes of Exposure: Inhalation, Skin absorption, Skin contact, Eye contact, Ingestion

Symptoms Related to Physical, Chemical and Toxicological Characteristics: Stomach or intestinal irritation, nausea, vomiting, diarrhea, irritation of the nose and airways, central nervous system depression, dizziness, drowsiness, weakness, fatigue, headache, unconsciousness, lack of coordination, confusion, skin irritation, redness, burning sensation, drying, cracking, other skin damage, eye irritation, stinging sensation, tearing, and swelling of the eyes. Swallowing large amounts may cause for material to enter the lungs during swallowing or vomiting, leading to lung inflammation and other lung damages.

Delayed and Immediate Effects & Chronic Effects from Exposure: The liquid defats the skin after long-term or repeated exposure. The substance may result in central nervous system depression symptoms, such as drowsiness or dizziness. This substance is a suspected skin sensitizer and may cause allergic skin reactions. This substance is a suspected respiratory sensitizer and may result in allergies, asthma symptoms or breathing difficulties. This substance is suspected of causing germ cell mutagenic effects based on studies on laboratory animals alone. This substance is suspected of damaging fertility or the unborn child based on laboratory animal studies. This substance may cause cancer to humans as outlined by OSHA, IARC, ACGIH, and NTP (see below).

Measures of Toxicity:

Acute toxicities are calculated based on component toxicities

Mixture: Acute Oral Toxicity: No sufficient data available

Acute Dermal Toxicity: No sufficient data available

Acute Inhalation Toxicity: LC₅₀ Rat: > 3,900 ppmV

Styrene

Acute Oral Toxicity

CAS # 100-42-5

LD₅₀ Rat: 2,650 mg/kg

Safety Data Sheet

Part Number: **9017481, 9017483**

Acute Inhalation Toxicity LC₅₀ Rat: 2,800 ppmV

Naphtha, petroleum CAS # **64742-95-6**
 Acute Oral Toxicity LD₅₀ Rat: > 4,000 mg/kg
 Acute Dermal Toxicity LD₅₀ Rabbit: > 3,480 mg/kg
 Acute Inhalation Toxicity LC₅₀ Rat: 3,670 ppmV

Dimethylaniline CAS # **121-69-7**
 Acute Oral Toxicity LD₅₀ Rat: 951 mg/kg
 Acute Dermal Toxicity LD₅₀ Rabbit: 1,770 mg/kg
 Acute Inhalation Toxicity LC₅₀ Rat: 250 mg/m³

Carcinogen Claims:

OSHA: **Yes; 2**

International Agency for Research on Cancer (IARC): **Yes; 2B [Possibly Carcinogenic]**

ACGIH: **No; A3 [Animal Carcinogen]**

National Toxicology Program (NTP) Report on Carcinogens: **Yes; II [Reasonably Anticipated Carcinogen]**

12. ECOLOGICAL INFORMATION

Eco-toxicity: This substance is expected to be toxic to aquatic organisms. It is strongly advised that this substance does not enter the environment. Local authorities should be advised if significant spillages cannot be contained or if material discharges into drains or ground water.

Styrene CAS # **100-42-5**
 Toxicity to Fish LC₅₀ – 4.02 mg/l (Fathead Minnow; 96 h)
 Toxicity to Daphnia EC₅₀ – 4.7 mg/l (Water flea; 48 h)
 Toxicity to Algae EC₅₀ > 4.9 mg/l (Green Algae; 72 h)

Dimethylaniline CAS # **121-69-7**
 Toxicity to Fish LC₅₀ – 65.6 mg/l (Fathead Minnow; 96 h)
 Toxicity to Daphnia EC₅₀ – 5 mg/l (Water Flea; 48 h)

Persistence & Degradability: No data available

Bio-accumulative Potential: No data available

Mobility in Soil: No data available

Other Adverse Effects: No data available

13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with Federal, State or Local regulations.
 Contaminated packaging should be emptied as far as possible before disposal.

Safety Data Sheet

Part Number: **9017481, 9017483**

14. TRANSPORT INFORMATION

DOT SHIPPING CLASSIFICATION:

UN NUMBER: UN1866
PROPER SHIPPING NAME: Resin solution, flammable
TRANSPORTATION HAZARD CLASS: 3
PACKING GROUP: III
HAZARD LABEL: 3

IMDG (Marine) SHIPPING CLASSIFICATION:

IMDG CODE: 3
UN NUMBER: UN1866
MARINE POLLUTANT: No
EmS: F-E; S-E
IMDG PACKING GROUP: III
HAZARD LABEL: 3

Description of the goods

RESIN SOLUTION flammable

IATA (Air) SHIPPING CLASSIFICATION:

ICAO/IATA-DGR: 3
UN NUMBER: UN1866
HAZARD LABEL: 3
IAO packing group: III

Description of the goods

Resin solution, flammable

15. REGULATORY INFORMATION

All components of this product conform to the following national inventory requirements. US TSCA, EU EINECS and Canada DSL

SARA Title III

Section 302 – Extremely Hazardous Chemicals

The following ingredients are subject to the supplier notification requirements of Section 302 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

None Listed

Section 313 – Toxic Chemicals

The following ingredients are subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (SARA/EPCRA) and the requirements of 40 CFR Part 37

Component	CAS #	Weight %	CERCLA RQ
Styrene	100-42-5	25 – 35	1,000

Safety Data Sheet

Part Number: **9017481, 9017483**

OTHER FEDERAL REGULATIONS

Components of this product are subject to RCRA Hazardous Waste requirements, Clean Air Act (CAA) Hazardous Air Pollutants requirements and OSHA Process Safety Management (PSM) high hazard requirements.

CANADIAN REGULATIONS

WHMIS Classification: B2, D2A, D2B (Based on components)

STATE REGULATIONS

California Proposition 65

WARNING: This product contains chemicals known to the state of California to cause cancer, birth defects, and other reproductive harm.

The components of this product may be included on the various state hazardous materials lists noted below.

California Hazardous Substances List
Delaware Air Quality Management List
Idaho Air Pollutants List
Illinois Toxic Air Contaminants List
Maine Hazardous Air Pollutants List
Massachusetts Hazardous Substances List
Michigan Critical Materials List
Minnesota Hazardous Substances List
New Jersey RTK Hazardous Substances List
New Jersey TCPA Extremely Hazardous Substances List
New York List of Hazardous Substances
North Carolina Toxic Air Contaminants List
Pennsylvania Hazardous Substances List
Washington Permissible Exposure Air Contaminants List
West Virginia Air Toxic Pollutants List
Wisconsin Hazardous Air Contaminants List

Note: Entries under Section 15 are not intended to be all inclusive of Federal and State laws and regulations. Please consult the appropriate agencies for further clarification of any requirements.



Safety Data Sheet

Part Number: **9017481, 9017483**

16. OTHER INFORMATION

This SDS conforms to the OSHA Hazard Communication Standard 1910.1200 published in the Federal Register March 26, 2012

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Shipping information may vary based upon container size and shipping destination. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage, or release to the environment. The manufacturer assumes no responsibility for injury to the recipient or third persons, or for any damages to any property resulting from misuse of the product.

Date of Issue/Revision: September 15, 2017.